



FloJak is easy to operate.

The FloJak "Plus" is a stainless-steel hand operated well-pump, capable of lifting well water up to 150 feet, delivering up to 10 GPM. The design is narrow and fits into almost any well, right above the existing submersible pump.

FloJak attaches to the top of the well casing with a heavy duty steel hanger-bracket, and is then covered with our canvas well bonnet, or a more permanent well-seal.

This system uses our high-resin, high pressure, PVC pipe in 5 foot lengths. FloJak is available in 50, 100 and 150 foot kits. You simply select a kit long enough to extend below the static water level in your well. If you need a longer system, you may order additional 50 foot pipe kits. FloJak kits are small and transportable, and assemble in less than an hour.

FloJak also manufactures lever-handles for our pumps that bolt right to the hanging bracket. These are designed to reduce work and increase pumping power. When lifting water over 70 feet you will require a PowerJak Lift Assist Kit. When pumping lesser depths we recommend the MiniJak Lever Arm. These lever arm handles are particularly essential if you plan to pump pressurized water directly into your home using a high pressure water hose (GatorHyde) connected to any two-way outdoor faucet. This is a convenience that can provide water for flushing or at the kitchen sink.

The shelf life is 25 years, and FloJak comes with a 2 year manufacturer's warranty. Every "below the water level" component is made from stainless steel or food grade polymers. FloJak is proudly Made in America, by Americans.



Pump & Pipe Kits



FP50 Pump Kit

- 50 Foot Pump Kit
- 40' Static or less
- Assembles in 30-60 minutes



E50 Pipe Kit

- 50 Feet Extension
- Includes 50' Pipe
- Assembles in 30-40 mins



FP100 Pump Kit

- 100 Foot Pump Kit
- 90' Static or
- Assembles in 40-60 minutes



FP150 Pump Kit

- 150 Foot Pump Kit
- 140' Static or less
- Assembles in 70-90 minutes



FP200 Pump Kit

- 200 Foot Pump Kit
- 190' Static or less
- Assembles in 90-110 minutes



FP250 Pump Kit

- 150 Foot Pump Kit
- 140' Static or less
- Assembles in 120 + minutes



TPAK-FP Pump Kit

- 100 Foot Pump Kit
- 90' Static or less
- Includes 6' & 50' GatorHyde Hoses
- Assembles in 40-60 minutes

Note- Visit www.flojak.com or request a printed pricing guide for prices.



Accessories



WS4 Seal

- 4" ABS Well Seal



WS6 Seal

- 6" ABS Well Seal



WS8 Seal

- 8" ABS Well Seal



GATORHYDE GH100 Hose

- 100 Feet High Pressure



GATORHYDE GH50 Hose

- 50 Feet High Pressure



GATORHYDE GH6 Hose

- 6 Feet High Pressure



MJ24

- MiniJak Pump Assist Handle with Stainless Handle



Well Bonnet

- Canvas well covering



BHV1

- Brass Hose Valve



BHA1

- 2-way hose adapter



WS97403

- Flojak Coated Gripper Gloves



PJP36

- PowerJak Pump Assist Handle
- 80% Pumping Effort Reduction

Contact Us

Flojak Hand Well Pumps, LLC

PO Box 957

408 Ironworks Drive

Mountain View, AR 72560

855-435-6525

www.flojak.com